

APPROVED SHEET

CUSTOMER: _____

CUSTOMER P/N: _____

JWD P/N:

S06E12BA

REV:

R1

DESCRIPTION:

10/100 BASE-TX

Meet AEC-Q200 Standard

Automotive Application

CUSTOMER APPROVAL		COMPANY APPROVAL	
INSPECTED BY:		ISSUED BY:	Bob
CHECKED BY:		CHECKED BY:	Mingrui Song
APPROVED BY:		APPROVED BY:	Focus, Wang
APPROVED DATE:		ISSUED DATE:	2022/11/11

Please Return One Copy to Us After Approved,TKS! (承认后请回寄一份,谢谢)

四川经纬达科技集团有限公司

Sichuan Jingweida Technology Group Co., Ltd

地址: 绵阳高新区防震减灾产业园

ADD: Protecting Against and Mitigating Earthquake Disasters Industrial Park,
High-tech Zone, Mianyang, Sichuan 621000 CHINA.

TEL: +86-816-2561202 FAX: +86-816-2562518

E-MAIL: myjwd@myjwd.com

WEB: www.myjwd.com









四川经纬达科技集团有限公司

Sichuan Jingweida Technology Group Co., Ltd


A. MECHANICAL(unit:mm)



Suggested PAD Layout



B. SCHEMATICS



DESCRIPTION	JWD P/N	SPEC NO.	REV: R1
10/100 BASE-TX	S06E12BA		PAGE: 1/3



四川经纬达科技集团有限公司

Sichuan Jingweida Technology Group Co., Ltd

C. ELECTRICAL SPECIFICATIONS @25°C

1. OCL(TD & RD): 475uH Min with 100 KHz, 0.1V@25°C
2. DCR(TX & RX): 1000mΩ Max
3. Turns Ratio:(1-3):(6-4)= 1CT:1.1CT±5%
4. Isolation Hipot: 3100VAC 1mA 2s
5. Operating temperature -40°C to +125°C
6. Storage Temperature(With Package): +10°C to +40°C
7. Storage Temperature(Without Package, Just For Components): -40°C to +125°C
8. RoHS Compliant
9. Qualification: Meet AEC-Q200




DESCRIPTION	JWD P/N	SPEC NO.	REV: R1
10/100 BASE-TX	S06E12BA		PAGE: 2/3





四川经纬达科技集团有限公司

Sichuan Jingweida Technology Group Co., Ltd


D. 包装信息(PACKAGE SPECIFICATION)





Four Reel



Inner Carton



Two Inner Carton



Export Carton

Package Quantity:

One Reel=800Pcs

One Inner Carton=800*4=3200Pcs

One Export Carton=3200*2=6400Pcs

DESCRIPTION	JWD P/N	SPEC NO.	REV: R1
10/100 BASE-TX	S06E12BA		PAGE: 3/3